

Distributor Stocking Part

Fox Part Number: FOXSDLF/040R




LEAD-FREE, RESISTANCE WELD, SMD, CRYSTAL
MODEL: HC49SDLF Series (please use FOXSDLF/040R/TR for full, 1k, reels)
 RoHS / REACH Compliant / Pb Free


A. Specifications

Parameters	
Frequency	4.000 MHz
Resonance Mode	Fundamental
Frequency Tolerance @ 25°C	±30 PPM Max
Frequency Stability, ref @ 25°C Over Operating Temp. Range	±50 PPM Max
Temperature Range Operating (T _{OPR}) Storage (T _{STG})	-40°C ~ +85°C -40°C ~ +125°C
Equivalent Series Resistance (ESR)	150 Ohms Max
Shunt Capacitance (C ₀) Absolute Maximum	7.0 pF
Load Capacitance (C _L)	20 pF
Drive Level	0.1 mW Max
Aging per year	±3 PPM Max
Maximum Soldering Temp / Time	260°C / 10 Seconds
Termination Finish (96.5%-3%-0.5%)	Sn – Ag – Cu
Moisture Sensitivity Level (MSL)	1
Weight (TYP)	649 mg


B. Mechanical / Dimensions (millimeters):



Marking Format



Tape and Reel Specification (mm)



NOTE: The above specifications, having been carefully prepared and checked, is believed to be accurate at the time of publication; however, no responsibility is assumed by Fox Electronics for inaccuracies.

Reference / Comments	Title / Description: Product Specifications		
Initial release	Drawing Number: DOC101002	Rev: 1	Size: A
	Part Number: FOXSDLF/040R		Page: 61429
	Draftsperson: AR	Approved: GB	Date: 05-20-2014